

HENKEL LOCTITE CORPORATION

12/08/02

ROCKY HILL, CONNECTICUT 06067
EMERGENCY PHONE: (860) 571-5100

MATERIAL SAFETY DATA SHEET

Page 01 of 06

Pro Strength Degreaser
30521

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: Pro Strength Degreaser
Item No.: 30521
Product Type: Aerosol cleaner

2. COMPOSITION, INFORMATION ON INGREDIENTS

Ingredients	CAS No.	%
Distillates (petroleum), hydrotreated light	64742-47-8	50-55
KEROSENE	8008-20-6	30-35
PROPANE	74-98-6	10-15

Ingredients which have exposure limits

Exposure Limits (TWA) Ingredients	ACGIH (TLV)	OSHA (PEL)	OTHER
Distillates (petroleum), hydrotreated light	None	None	300ppm
PROPANE	2500 ppm	1000 ppm 1800 mg/m3	None

Exposure Limits (STEL) Ingredients	ACGIH (TLV)	OSHA (PEL)
PROPANE	Asphyxiant	Asphyxiant

3. HAZARDS IDENTIFICATION

Toxicity: Irritation of eyes, skin and respiratory system. May cause nervous system depression. Extreme overexposure may result in unconsciousness and possibly death. Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.

Primary Routes of Entry: Exposure may be by inhalation and/or skin or eye contact, depending on conditions of use. To minimize exposure, follow recommendations for proper use, ventilation, and personal protective equipment.

Signs and Symptoms of Exposure: Headache, dizziness, nausea, and loss of coordination are indications of excessive exposure to vapors or spray mists. Redness and itching or

HENKEL LOCTITE CORPORATION

12/08/02

ROCKY HILL, CONNECTICUT 06067

MATERIAL SAFETY DATA SHEET

Page 03 of 06

Product Name: Pro Strength Degreaser
Item No.: 30521

5. FIRE FIGHTING MEASURES

(continued)

possible autoignition or explosion when exposed to extreme heat.

Hazardous Products formed

by Fire or Thermal Decomp Irritating organic vapors; oxides of carbon.

Unusual Fire or

Explosion Hazards:

Isolate from heat, electrical equipment, sparks, and open flame. Closed containers may explode when exposed to extreme heat. Application to hot surfaces requires special precautions. During emergency conditions overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

Explosive Limits:

(% by volume in air) Lower 0.6%

(% by volume in air) Upper 9.5%

6. ACCIDENTAL RELEASE MEASURES

Steps to be taken in case of spill or leak:

Remove sources of ignition. Maintain good ventilation. Soak up with an inert absorbent. Store in a closed container until disposal.

7. HANDLING AND STORAGE

Safe Storage:

(Contact Loctite Customer

Handling:

Keep away from heat, sparks, and open flame. Service 1-800-243-4874 for shelf life information) Keep away from heat, sparks or open flame. Vapors will accumulate readily and ignite explosively. Use only with adequate ventilation. Avoid breathing vapors and spray mists. Avoid contact with skin and eyes. During use and until all vapors are gone: Keep area ventilated. Do not smoke. Extinguish all flames, pilot lights, and heaters. Turn off stoves, electric tools and appliances, and other sources of ignition. Consult NFPA Code. Use approved bonding and grounding procedures. Do not puncture, incinerate, or expose to temperature above 120°F. Heat from sunlight radiators, stoves, hot water, and other heat sources could cause container to burst. Do not take internally. Keep out of the reach of children. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. Wash hands after using.

HENKEL LOCTITE CORPORATION

12/08/02

ROCKY HILL, CONNECTICUT 06067
EMERGENCY PHONE: (860) 571-5100

MATERIAL SAFETY DATA SHEET

Page 04 of 06

Product Name: Pro Strength Degreaser
Item No.: 30521

8. EXPOSURE CONTROLS, PERSONAL PROTECTION

Eyes: Wear safety spectacles with unperforated sideshields.
Skin: Rubber or plastic chemical resistant gloves.
Ventilation: Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section 2 is maintained below applicable exposure limits. Refer to OSHA Standards 1910.94, 1910.107, 1910.108.
Respiratory: If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic/particulate respirator approved by NIOSH/MSHA for protection against materials in Section 2.

See Section 2 for Exposure Limits.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Yellow liquid
Odor: Mild petroleum
Boiling Point: Range: Less than 0°F to 572°F
pH: Does not apply
Solubility in Water: Not available
Specific Gravity: 0.76 (Base only)
Volatile Organic Compound (EPA Method 24): 96.50%; 733 grams per liter of material less exempt solvents
Vapor Pressure: Not available
Vapor Density: More than 1 (base only)
Evaporation Rate (Ether = 1): Faster

10. STABILITY AND REACTIVITY

Stability: Stable
Hazardous Polymerization: Will not occur
Incompatibility: None
Conditions to Avoid: Not available
Hazardous Decomposition Products (non-thermal): None

11. TOXICOLOGICAL INFORMATION

See Section 3.

HENKEL LOCTITE CORPORATION

12/08/02

ROCKY HILL, CONNECTICUT 06067
EMERGENCY PHONE: (860) 571-5100

MATERIAL SAFETY DATA SHEET

Page 05 of 06

Product Name: Pro Strength Degreaser
Item No.: 30521

12. ECOLOGICAL INFORMATION

No data available

13. DISPOSAL CONSIDERATIONS

Recommended methods of
disposal:Incinerate liquid obtained by spray-emptying cans
following EPA and local regulations. Do not
puncture or incinerate pressurized cans.EPA Hazardous Waste
Number

D001 - Hazardous waste per 40CFR 261.21

14. TRANSPORTATION INFORMATION

DOT (49 CFR 172)

Domestic Ground Transport

Proper Shipping Name: Consumer Commodity

Hazard Class or

Division: ORM-D

Identification Number: None

Marine Pollutant: None

IATA

Proper Shipping Name: Aerosols, flammable

Class or Division: Division 2.1

UN or ID Number: UN 1950

15. REGULATORY INFORMATION

CA Proposition 65:

No California Proposition 65 chemicals are known
to be present.

16. OTHER INFORMATION

Estimated NFPA(R) Code:

Health Hazard: 2

Fire Hazard: 4

Reactivity Hazard: 0

Specific Hazard: Does not apply

Estimated HMIS(R) Code:

Health Hazard: 2*

Flammability Hazard: 4

Reactivity Hazards: 0

Personal Protection: See Section 8.

NFPA is a registered trademark of the National Fire Protection Assn.

HMIS is a registered trademark of the National Paint and Coatings Assn.

Prepared By:

Louis Fabrizio

HENKEL LOCTITE CORPORATION

12/08/02

ROCKY HILL, CONNECTICUT 06067
EMERGENCY PHONE: (860) 571-5100

MATERIAL SAFETY DATA SHEET

Page 06 of 06

Product Name:

Pro Strength Degreaser

Item No.:

30521

16. OTHER INFORMATION

(continued)

Title: Regulatory Affairs Specialist
Company: Henkel Loctite Corporation, Rocky Hill CT 06067
(24hr.) Phone: (860) 571-5100
Revision Date: March 14, 2002 Revision: 0003

[application assistance](#) . [browse catalog](#) . [troubleshooting](#) . [equipment](#)
[datasheets](#) . [distributor locator](#) . [what's new](#) . [career opportunities](#)
[about loctite](#) . [contact loctite](#) . [literature](#) . [loctite world wide](#) . [search](#) . [home](#)
copyright © 1997-2000 Loctite