

=====

MATERIAL SAFETY DATA SHEET (SUBSTITUTES FOR OSHA FORM 174): May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200.

=====

PRODUCT NUMBER: 554
IDENTITY: DEFENSE EF

Revision Date: 01/19/2007

Section I

Manufacturer's Name:	QUEST CHEMICAL CORPORATION	Telephone Numbers:
Address:	12255 FM 529	Emergency:
	NORTHWOODS INDUSTRIAL PARK	800/255-3924
	HOUSTON	Information:
State:	TX Zip Code:77041	713/8968188

HMIS CODES: REACTIVITY: 1 FLAMMABILITY: 3 HEALTH: 1 PERSONAL PROTECT: A

Section II: HAZARDOUS INGREDIENTS/IDENTITY INFORMATION (All of the ingredients contained in this product are listed on the TSCA inventory.)

=====

Name	Cas No.	OSHA PEL	ACGIH TLV	OTHER LIM	%
HEPTANE	142-82-5	400 PPM	400 PPM	N/A	_____
MINERAL SPIRITS	8052-41-3	500 PPM	100 PPM		_____
PROPANE/N-BUTANE	68476-86-8	1000 PPM	600 PPM	N/A	_____
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____

Section III: PHYSICAL/CHEMICAL CHARACTERISTICS

=====

Boiling Point:	156	Specific Gravity (water=1)	0.76
Vapor Pressure (mm Hg)	124	Melting Point:	N/A
Vapor Density (AIR=1)	>1	Evaporation Rate:	5
Solubility in Water:	0%	(Butyl Acetate=1)	

Appearance and Odor: BROWN COLOR, PETROLEUM SOLVENT ODOR

Section IV: FIRE AND EXPLOSION HAZARD DATA

=====

Flash Point (Method Used): 150 F TCC Flammable Limits: LEL: 1.1 UEL: 7.5
Extinguishing Media: STANDARD DRY CHEMICAL FIRE EXTINGUISHER
Special Fire Fighting Procedures: SELF CONTAINED BREATHING APPARATUS

Unusual Fire and Explosion Hazards: FLAMMABLE. CONTENTS UNDER PRESSURE. EXPOSURE TO TEMPERATURES ABOVE 120 F MAY CAUSE BURSTING. MAY DEVELOP A FLAMMABLE ATMOSPHERE IN CONFINED AREAS.

Stability: Unstable: Conditions to avoid:
Stable: X TEMPERATURES ABOVE 120 F, HOT SURFACES
Incompatibility (Materials to Avoid): SOME PLASTICS

Hazardous Decomposition or Byproducts: NONE KNOWN

Hazardous Polymerization: May Occur: Will Not Occur: X
Conditions to Avoid: NONE KNOWN

Section VI: HEALTH HAZARD DATA

Routes of Entry: Inhalation: YES Skin: YES Ingestion: YES
Health Hazards (Acute and Chronic):
INHALATION: NAUSEA, LIGHT HEADEDNESS. SKIN OR EYES: WILL CAUSE IRRITATION.
INGESTION: NAUSEA, VOMITING, LOSS OF CONSCIOUSNESS.

Carcinogenicity: NTP:NO IARC Monographs:NO OSHA Reg:NO
Signs and Symptoms of Exposure: SEE HEALTH HAZARDS

Medical Conditions Generally Aggravated by Exposure: EXCESSIVE EXPOSURE
WILL AGGRAVATE RESPIRATORY, CARDIOVASCULAR OR PULMONARY ILLNESS.

Emergency and First Aid Procedures: INHALATION: REMOVE TO FRESH AIR.
INGESTION: DO NOT INDUCE VOMITING. CONTACT PHYSICIAN. SKIN: WASH WITH SOAP
AND WATER. IF IRRITATION PERSISTS, CONTACT PHYSICIAN.

Section VII: PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to be Taken in Case Material is Released or Spilled: WIPE UP WITH
RAG OR USE SOME ABSORBENT CLAY MATERIAL.

Waste Disposal Method: DISPOSE OF RESIDUE IN ACCORDANCE WITH FEDERAL,
STATE AND LOCAL GUIDELINES. DO NOT REUSE EMPTY CONTAINER. DO NOT PUNCTURE
OR INCINERATE CONTAINER.

Precautions to be Taken in Handling and Storing: DO NOT STORE NEAR HEAT
OR OPEN FLAME. EXPOSURE TO TEMPERATURES ABOVE 120 F MAY CAUSE BURSTING.

Other Precautions: VAPOR MAY COLLECT IN LOW LYING AREAS.

Section VIII: CONTROL MEASURES

Respiratory Protection: USE ONLY IN WELL VENTILATED AREAS
Ventilation: Local Exhaust: YES
Mechanical: N/A Special: N/A
Other: N/A
Protective Gloves: N/A
Eye Protection: SAFETY GOGGLES ARE RECOMMENDED WHENEVER CHEMICALS ARE USED.
Other Protective Clothing or Equipment:
N/A
Work/Hygienic Practices:
WASH HANDS AFTER USE.