

MATERIAL SAFETY DATA SHEET

DATE PRINTED: 7/12/2004
 Kevin Banks

PAGE 1

SECTION 1. CHEMICAL PRODUCT AND COMPANY INFORMATION

MANUFACTURERS NAME W.M. BARR & COMPANY, INC. **ADDRESS** 2105 Channel Ave. Memphis, TN 38113 USA
EMERGENCY TELEPHONE #1 901-775-0100 **EMERGENCY CONTACT** W.M. Barr Technical Services

EMERGENCY INFORMATION
 "3E" 24 HOUR MEDICAL EMERGENCY #, 800 451-8346.
 SEE SECTION 5 FOR ADDITIONAL EMERGENCY INFORMATION

INVENTORY ITEM #
 GGT69

PRODUCT NAME
 KS TURPENTINE 1 GL

REVISED BY W.M. Barr Technical Services **REVISION DATE** 7/30/2003

SECTION 2. COMPOSITION/INFORMATION ON INGREDIENTS

SUBSTANCE DESCRIPTION	PERCENT	CAS#	CARCINOGENICITY			
			NTP	ACGIH	OSHA	IARC
TURPENTINE	95-100	8006-64-2	N	N	N	N

SECTION 3. REGULATORY INFORMATION

EXPOSURE LIMITS/REGULATORY INFORMATION

SUBSTANCE DESCRIPTION	REG.AGCY U/M		TWA	STEL	CEIL	SKIN	PEL
	ACGIH	OSHA					
TURPENTINE	PPM	100.00	100.00	N/E	N/E	N	N/E
	PPM	100.00					

ADDITIONAL REGULATORY INFO
 The time weighted average (TWA) value described herein is a threshold limit value (TLV) as established by ACGIH. The permissible exposure limit (PEL) is a value established by OSHA.

CALIFORNIA (PROPOSITION #65)
 Ingredients in this product are not listed on California's Prop 65 list: "Chemicals Known to the State to Cause Cancer or Reproductive Toxicity."

SEC. 313 SUPPLIER NOTIFICATION
 The following information must be included in all MSDS that are copied and distributed for this material.

This product contains no chemicals subject to the reporting requirements of SARA III: Section 313.

CLEAN AIR ACT
 This formula contains no known ozone depleting chemicals.

HAZARD COMMUNICATION STANDARD
 This document is prepared in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200). This MSDS contains thirteen (13) sections.

MATERIAL SAFETY DATA SHEET

DATE PRINTED: 7/12/2004
Kevin Banks

PAGE 2

SECTION 3. REGULATORY INFORMATION
(CONTINUED)

The following effects and/or symptoms are not expected to be experienced by persons who use this product properly and according to ALL instructions, precautions, and warnings; however, should the product user experience ANY questionable effects or symptoms, the product user should immediately seek medical attention.

SECTION 4. HAZARDS IDENTIFICATION
-----**INHALATION ACUTE EXPOSURE EFFECTS**

May cause dizziness, headache, watering of eyes, irritation of respiratory tract, nausea, depression of central nervous system, and serious irritation to kidneys. Severe overexposure may cause unconsciousness.

SKIN CONTACT ACUTE EXPOSURE EFFECTS

None known.

EYE CONTACT ACUTE EXPOSURE EFFECTS

This material is an eye irritant.

INGESTION ACUTE EXPOSURE EFFECTS

Harmful or fatal if swallowed. May cause nausea, vomiting, gastrointestinal irritation, and diarrhea.

CHRONIC EXPOSURE EFFECTS

Reports have associated repeated and prolonged overexposure to solvents with neurological and other physiological damage. May cause headache, anorexia, anxiety, skin irritation, excitement, tinnitus, permanent central nervous system changes, mental confusion, convulsions, coma, and death.

MEDICAL CONDITIONS AGGRAVATED

None known.

PRIMARY ROUTE OF EXPOSURE

Inhalation, ingestion, and dermal.

SECTION 5. FIRST AID MEASURES
-----**INHALATION**

If user experiences breathing difficulty, move to air free of vapors. Administer oxygen or artificial respiration until medical assistance can be rendered.

SKIN CONTACT

Wash with soap and water.

EYE CONTACT

Flush with large quantities of water for at least 15 minutes and seek immediate medical attention.

INGESTION

DO NOT induce vomiting. Call your poison control center, hospital emergency room, or physician immediately.

NOTE TO PHYSICIAN

This formula is registered with POISINDEX.
Call your local poison control center for further information.

SECTION 6. FIRE FIGHTING MEASURES

MATERIAL SAFETY DATA SHEET

DATE PRINTED: 7/12/2004
Kevin Banks

PAGE

3

SECTION 6. FIRE FIGHTING MEASURES
(CONTINUED)

HAZARD RATING SOURCE	HMIS	NFPA
HEALTH	2	1
FLAMMABILITY	3	3
REACTIVITY	0	0
OTHER	G	NA

FLASH METHOD

Seta

FLASH POINT

94.00 F 34.44 C

LOWER EXPLOSION LIMIT

0.82

GENERAL COMMENTS

OSHA FLAMMABILITY: Class IC

EXTINGUISHING METHOD

Use carbon dioxide, dry powder, or foam.

FIRE FIGHTING PROCEDURES

Self-contained respiratory protection should be provided for fire fighters fighting fires in buildings or confined areas. Storage containers exposed to fire should be kept cool with water spray to prevent pressure build-up. Stay away from heads of containers that have been exposed to intense heat or flame.

FIRE AND EXPLOSION HAZARDS

DANGER! FLAMMABLE. KEEP AWAY FROM HEAT, SPARKS, FLAME, AND ALL OTHER SOURCES OF IGNITION. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and all other sources of ignition during use and until all vapors are gone. Beware of static electricity that may be generated by synthetic clothing and other sources.

SECTION 7. ACCIDENTAL RELEASE MEASURES

CLEAN-UP

Keep unnecessary people away; isolate hazard area and deny entry. Stay upwind, out of low areas, and ventilate closed spaces before entering. Shut off ignition sources; keep flares, smoking or flames out of hazard area. SMALL SPILLS: take up liquid with sand, earth or other noncombustible absorbent material and place in a plastic container where applicable. LARGE SPILLS: dike far ahead of spill for later disposal.

For transportation related spills contact Chemtrec at 1-800-424-9300 for emergency assistance.

WASTE DISPOSAL

Dispose in accordance with applicable local, state and federal regulations.

SECTION 8. HANDLING AND STORAGE

MATERIAL SAFETY DATA SHEET

DATE PRINTED: 7/12/2004
Kevin Banks

PAGE

4

SECTION 8. HANDLING AND STORAGE
(CONTINUED)
-----**STORAGE**

Keep container tightly closed when not in use. Store in a cool, dry place. Do not store near flames or at elevated temperatures.

HANDLING

Read carefully all cautions and directions on product label before use. Since empty container retains residue, follow all label warnings even after container is empty. Dispose of empty container according to all regulations. Do not reuse this container.

SECTION 9. TRANSPORT INFORMATION
-----**TRANSPORTATION**

DOMESTIC: TURPENTINE, 3, UN1299, PGIII

IMDG: TURPENTINE, 3, UN1299, PGIII, Flashpoint 111F (43.88C) EMS 3-07

IATA: Turpentine, 3, UN1299, PGIII, Flashpoint 111F (43.88C) ERG Code
3L

SECTION 10. EXPOSURE CONTROLS/PERSONAL PROTECTION
-----**VENTILATION PROTECTION**

Use only with adequate ventilation to prevent build-up of vapors. Open all windows and doors. Use only with a cross ventilation of moving fresh air across the work area. If strong odor is noticed or you experience slight dizziness, headache, nausea, or eye-watering - STOP - ventilation is inadequate. Leave area immediately.

RESPIRATORY PROTECTION

For OSHA controlled work place and other regular users - Use only with adequate ventilation under engineered air control systems designed to prevent exceeding appropriate TLV. For occasional use, where engineered air control is not feasible, use properly maintained and properly fitted NIOSH approved respirator for organic solvent vapors. A dust mask does not provide protection against vapors.

SKIN PROTECTION

Wear impermeable gloves. Gloves contaminated with product should be discarded. Promptly remove clothing that becomes soiled with product.

EYE PROTECTION

Safety glasses, chemical goggles or face shields are recommended to safeguard against potential eye contact, irritation, or injury. Contact lenses should not be worn while working with chemicals.

OTHER PROTECTION

Various application methods can dictate use of additional protective safety equipment, such as impermeable aprons, etc., to minimize exposure. A source of clean water should be available in the work area for flushing eyes and skin. Do not eat, drink, or smoke in the work area. Wash hands thoroughly after use. Before reuse, thoroughly clean any clothing or protective equipment that has been contaminated by prior use. Discard any clothing or other protective equipment that cannot be decontaminated, such as gloves or shoes.

SECTION 11. PHYSICAL AND CHEMICAL PROPERTIES

MATERIAL SAFETY DATA SHEET

DATE PRINTED: 7/12/2004
Kevin Banks

PAGE

5

SECTION 11. PHYSICAL AND CHEMICAL PROPERTIES
(CONTINUED)
-----**VOLATILE %**
100.000
by weight**BOILING POINT**
GT 309.00 F 153.88 C BOILING RANGE: 309 F - 338 F**VAPOR DENSITY (Air = 1.0)**
Heavier than air**EVAPORATION RATE**
Slower than ether**BULK DENSITY**
7.189
lbs/gal at 75 F**pH FACTOR**
N/E**PHOTOCHEMICALLY REACTIVE**
YES**MAX V.O.C.**
862 grams per liter (excluding exempt solvents & water)**MAX VAPOR PRESSURE**
(of the V.O.C.) 4mm Hg at 20 degrees C-----
SECTION 12. STABILITY AND REACTIVITY
-----**INCOMPATIBILITIES**
Incompatible with strong oxidizing agents.**DECOMPOSITION**
Decomposition may produce carbon monoxide and carbon dioxide.**POLYMERIZATION**
Will not occur.**STABILITY**
Stable.-----
SECTION 13. ADDITIONAL INFORMATION
-----**IMPORTANT NOTE**
The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.**LEGEND:**
PPM = parts per million
MG/M3 = milligrams per cubic meter
N/E or NE = none established
GT = greater than
N/A or NA = not applicable

MATERIAL SAFETY DATA SHEET

DATE PRINTED: 7/12/2004
Kevin Banks

PAGE

6

SECTION 13. ADDITIONAL INFORMATION
(CONTINUED)

TCC = tag closed cup
TOC = tag open cup
PMCC = Pensky-Martens closed cup
IDLH = Immediately Dangerous to Life and Health

END OF MSDS