

# Material Safety Data Sheet



Zep, Inc.  
1310 Seaboard Industrial Blvd.  
Atlanta, GA 30318  
1-877-I-BUY-ZEP (428-9937)  
www.zep.com

## Section 1. Chemical Product and Company Identification

**Product name** ML LUBRICANT  
**Product use** Aerosol Lubricant  
**Product code** 7313  
**Date of issue** 08/27/10 **Supersedes** 08/05/09

### Emergency Telephone Numbers

**For MSDS Information:**  
Compliance Services 1-877-I-BUY-ZEP (428-9937)

**For Medical Emergency**  
(877) 541-2016 Toll Free - All Calls Recorded

**For Transportation Emergency**  
CHEMTREC: (800) 424-9300 - All Calls Recorded  
In the District of Columbia (202) 483-7616

**Prepared By**  
Compliance Services  
1420 Seaboard Industrial Blvd.  
Atlanta, GA 30318

Printing date: 08/31/10

## Section 2. Hazards Identification

### Emergency overview

\*Hazard Determination System (HDS): Health, Flammability, Reactivity

**DANGER !**



FLAMMABLE LIQUID AND VAPOR. Vapor may cause flash fire. Do not smoke. CAUSES EYE, SKIN AND RESPIRATORY TRACT IRRITATION. VAPOR HARMFUL. CONTENTS UNDER PRESSURE.

**NOTE:** MSDS data pertains to the product as delivered in the original shipping container(s). Risk of adverse effects are lessened by following all prescribed safety precautions, including the use of proper personal protective equipment.

### Acute Effects

#### Routes of Entry

Dermal contact. Inhalation.

**Eyes** Causes eye irritation. Inflammation of the eye is characterized by redness, watering and itching.

**Skin** Causes skin irritation. Skin inflammation is characterized by itching, scaling, or reddening.

**Inhalation** Over-exposure by inhalation may cause respiratory irritation. Inhalation causes headaches, dizziness, drowsiness and nausea and may lead to unconsciousness. Can cause central nervous system (CNS) depression.

**Ingestion** Harmful if swallowed. Aspiration hazard if swallowed. Can enter lungs and cause damage.

### Chronic effects

Overexposure of this product by inhalation or absorption can produce central nervous system depression resulting in headache, nausea and/or dizziness. Contains material which may cause damage to the following organs: central nervous system (CNS).

### Carcinogenicity

Ingredients: Not listed as carcinogen by OSHA, NTP or IARC.

### Product/ingredient name

ACGIH

IARC

EPA

NIOSH

NTP

OSHA

Asphalt (Petroleum)

A4

3

-

+

-

-

**Additional Information:** See Toxicological Information (Section 11)

## Section 3. Composition/Information on Ingredients

### Name of Hazardous Ingredients

CAS number

% by Weight

ASPHALT (Petroleum)

8052-42-4

35 - 45

HYDROCARBON PROPELLANT; blend of propane and n-butane

74-98-6; 106-97-8

10 - 20

PARAFFIN OIL; blend of heavy and light naphthenic petroleum distillate

64742-52-5

1 - 10

ISOPARAFFINIC SOLVENT; hydrotreated light distillate (petroleum); C12-C14 isoalkanes

68551-19-9

1 - 10

## Section 4. First Aid Measures

**Eye Contact** Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention immediately.

**Skin Contact** Wash affected area with soap or mild detergent and water. Remove contaminated clothing and shoes. Wash clothing before reuse. Get medical attention if irritation develops.

**Inhalation** Move exposed person to fresh air. If irritation persists, get medical attention.

**Ingestion** Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. Get medical attention immediately.

### Section 5. Fire Fighting Measures

National Fire Protection Association (U.S.A.)



**Flash Point** Not available.

**Flammable Limits** Not determined.

**Flammability** FLAMMABLE. (CSMA method)

**Fire hazard** CONTENTS UNDER PRESSURE. In a fire or if heated, a pressure increase will occur and the container may burst. Bursting aerosol containers may be propelled from a fire at high speed. May emit toxic fumes under fire conditions.

**Fire-Fighting Procedures** Use an extinguishing agent suitable for the surrounding fire.

### Section 6. Accidental Release Measures

**Spill Clean up** Large spills are unlikely due to packaging.

### Section 7. Handling and Storage

**Handling** Put on appropriate personal protective equipment (see section 8). Store and use away from heat, sparks, open flame or any other ignition source. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wash thoroughly after handling. Empty containers retain product residue and can be hazardous.

**Storage** CONTENTS UNDER PRESSURE. Do not puncture, incinerate, store the container at temperatures above 49°C (120°F) or in direct sunlight. Keep out of the reach of children.

### Section 8. Exposure Controls/Personal Protection

#### Product name

ASPHALT (Petroleum)

#### Exposure limits

**NIOSH REL (United States, 6/2009).**

CEIL: 5 mg/m<sup>3</sup> 15 minute(s). Form: Fume

**OSHA PEL (United States).**

TWA: 100 ppm 8 hour(s).

**ACGIH TLV (United States).**

TWA: 100 ppm 8 hour(s).

**ACGIH TLV (United States, 2/2010).**

TWA: 0.5 mg/m<sup>3</sup>, (as benzene soluble aerosol) 8 hour(s). Form: Inhalable fraction. See Appendix C, paragraph A. Inhalable Particulate Mass TLVs (IPM-TLVs) for those materials that are hazardous when deposited anywhere in the respiratory tract.

PARAFFIN OIL; blend of heavy and light naphthenic petroleum distillate

**OSHA PEL (United States).**

TWA: 5 mg/m<sup>3</sup> 8 hour(s). Form: Mist

**ACGIH TLV (United States).**

TWA: 5 mg/m<sup>3</sup> 8 hour(s). Form: Mist

**NIOSH REL (United States, 6/2009).**

TWA: 5 mg/m<sup>3</sup> 10 hour(s). Form: Mist

STEL: 10 mg/m<sup>3</sup> 15 minute(s). Form: Mist

ISOPARAFFINIC SOLVENT; hydrotreated light distillate (petroleum); C12-C14 isoalkanes

**NIOSH REL (United States).**

TWA: 1200 mg/m<sup>3</sup> Form: Vapor

#### Personal Protective Equipment (PPE)

**Eyes** Safety glasses.



**Body** Wear appropriate protective clothing to prevent skin contact. Recommended: Neoprene gloves. Nitrile gloves.

**Respiratory** Use with adequate ventilation. Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective occupational exposure limits. Wear appropriate respirator when ventilation is inadequate.

### Section 9. Physical and Chemical Properties

**Physical State** Aerosol. Viscous, Oily liquid.

**Color** Black.

**pH** Not available.

**Odor** Solvent-like.

**Boiling Point** >200°C (>392°F)

**Vapor Pressure** Not determined.

**Specific Gravity** 0.904

**Vapor Density** Not determined.

**Solubility** Insoluble in the following materials: cold water and hot water.

**Evaporation Rate** Not determined.

**VOC (Consumer)** 14.98% 1.13 (lb/gal) 135 g/l

**Section 10. Stability and Reactivity**

<b>Stability and Reactivity</b>	The product is stable.
<b>Incompatibility</b>	Keep away from heat, sparks and flame. Reactive or incompatible with the following materials: oxidizing materials.
<b>Hazardous Polymerization</b>	Will not occur.
<b>Hazardous Decomposition Products</b>	carbon oxides (CO, CO <sub>2</sub> )

**Section 11. Toxicological Information****Acute Toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
Asphalt (Petroleum)	LD50 Oral	Rat	>5000 mg/kg	-
Isoparaffinic Solvent; Hydrotreated light distillate (petroleum)	LD50 Dermal	Rabbit	>2000 mg/kg	-
	LD50 Oral	Rat	>2000 mg/kg	-

**Section 12. Ecological Information**

**Environmental Effects** Not available.

**Aquatic Ecotoxicity**

Not available.

**Section 13. Disposal Considerations****Waste Information**

Waste must be disposed of in accordance with federal, state and local environmental control regulations. Consult your local or regional authorities for additional information.

**Waste Stream** Code: D001  
Classification: - [Hazardous waste.]  
Origin: - [RCRA waste.]

**Section 14. Transport Information**

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label
<b>DOT Classification</b>		Consumer commodity	ORM-D	-	
<b>IMDG Class</b>					

**NOTE:** DOT classification applies to most package sizes. For specific container size classifications or for size exceptions, refer to the Bill of Lading with your shipment.

PG\* : Packing group

**Section 15. Regulatory Information****U.S. Federal Regulations**

SARA 313 toxic chemical notification and release reporting:

No products were found.

**Clean Water Act (CWA) 307:** No products were found.

**Clean Water Act (CWA) 311:** No products were found.

**Clean Air Act (CAA) 112 regulated toxic substances:** No products were found.

All Components of this product are listed or exempt from listing on TSCA Inventory.

**State Regulations**

**California Prop 65** No products were found.

**Section 16. Other Information**

*To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein.*

*Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.*

\*NOTE: Hazard Determination System (HDS) ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although these ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HDS ratings are to be used with a fully implemented program to relay the meanings of this scale.